

TYRES

Product group	Tyres
Item number	72200263
Valid tyre size	320 / 85 R 32
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Sonderpostenkategorie	Disassambled
type of damage	Hole in the flank



Mitas

Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.



Technical Informations

Item number	72200263
Valid tyre size	320 / 85 R 32
Alternative size 1	12.4R32
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	64,40
Recommended rim size	9
Permitted rim size	10, 11
Maximum air pressure [bar].	4,00
Section width (mm)	309
Outer diameter of tyre [mm].	1365
Stat. radius (SLR) [mm]	625
Rolling circumference [mm].	4035
Tread depth (mm)	40,0
Number of lugs	22x2
Lug width (mm)	40
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		4,00	
142 B	2650	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.