

## **TYRES**

Product group	Tyres	
Item number	72200277	
Valid tyre size	15 x 4.5 - 8	
Brand	ВКТ	
Tread pattern	Maglift	
Sonderpostenkategorie	Disassambled	
type of damage	Pollution	





## Notes and features

- High-quality, 3 layer rubber compound (tread pattern, suspension, basis compound) speaks for the modern, solid rubber tyre design and provides smoothness and ride comfort.
- 4 steel ring packs in the base compound ensure optimal, solid fitting to the rim.
- The hard-wearing tread compound distinguishes itself through a cut-, notch- and heat-resistant compound with high mileage and even wear.
- The BKT Maglift solid rubber tyre, available in standard and LIP design, offers an excellent price-performance
- All Maglift solid tyres are built in such a way to dissipate static charge from the vehicle.



## **Technical Informations**

Item number	72200277	
Valid tyre size	15 x 4.5 - 8	
Brand	ВКТ	
Tread pattern	Maglift	
Carcass properties	cass properties STD,Non-Marking,Solid Rubber	
Antistatic	No	
Tyre colour	Grey	
Nettogewicht [kg] (gültig)	9,64	
Recommended rim size	3.00D	
Section width (mm)	119	
Side panel width [mm]	117	
Tread width (mm)	103	
Overall width [mm].	118.5	
Outer diameter of tyre [mm].	378	
Tread depth (mm)	14,5	
E-Ready	No	

## Load capacity

Ind	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	1040	25	Load wheel		
	800	25	Steering wheel		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.