

TYRES

Product group	Tyres
Item number	72200436
Valid tyre size	18.00 - 33
LI / SI / PR	40 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	SM 54
Sonderpostenkategorie	Disassambled
type of damage	Cut in the flank





Notes and features

- The smooth and extra deep L-4S tread pattern is ideally suited to handling empty and loaded containers, especially on hard surfaces.
- The tread pattern consists of a highly wear- and cutresistant rubber compound.
- Due to its extra deep, smooth tread pattern design, the tyre offers excellent ride comfort and outstanding stability in lift mode.



Technical Informations

Item number	72200436
Valid tyre size	18.00 - 33
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	SM 54
TRA Code	L4S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	529,80
Recommended rim size	13.00/2.5
Maximum air pressure [bar].	10,30
Section width (mm)	535
Outer diameter of tyre [mm].	1895
Stat. radius (SLR) [mm]	840
Rolling circumference [mm].	5609
Tread depth (mm)	59,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	26655	10		10,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.