

WHEELS

Product group	Wheels
Item number	72200443
Valid wheel size	445 / 45 R 19.5
Brand	Linglong
Tread pattern	KXA408
Valid rim size	14.00 x 19.5
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	4875
Speed complete wheel [km/h]	65
Sonderpostenkategorie	Disassembled
type of damage	Dismounted,Runout
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No

Technical Informations

LI / SI / PR	164 D, 24 PR
Load capacity 1 [kg]	5000
Speed 1 [km/h].	65
M+S	M+S
Antistatic	No
Nettogewicht [kg] (gültig)	109,13
Section width (mm)	446
Stat. radius (SLR) [mm]	415
Rolling circumference [mm].	2712

Tread depth (mm)	16,0
E-Ready	No
Load capacity of rim 1 [kg]	5450
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	65
Maximum air pressure [bar].	9,00
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve

Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade