

TYRES

Product group	Tyres
Item number	72200451
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344
Sonderpostenkategorie	Disassembled
type of damage	Dismounted, Vulcanization errors



Notes and features

- The Alliance Forestar 344 is a powerful forestry tyre for CTL machines.
- The steel-reinforced nylon casing, the special rubber compound, as well as the reinforced sidewalls, protect the tyre against punctures.
- The traction tread pattern with low-angled lugs provides excellent grip and good self-cleaning thanks to wide gaps between the lugs.
- Due to the close spacing of the lugs in the centre of the tread, the rolling resistance can be reduced on hard surfaces.
- Matching chains and ribbons are available on the market.

Technical Informations

Item number	72200451
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	209,40
Recommended rim size	24.00
Maximum air pressure [bar].	5,00
Section width (mm)	710
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	620
Rolling circumference [mm].	4016
Tread depth (mm)	50,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A2	6900	10		5,00	
168 A8	5600	40		5,00	