Bohnenkamp Moving Professionals

14.03.2025

TYRES

Product group	Tyres	
Item number	72200451	
Valid tyre size	710 / 45 - 26.5	
LI / SI / PR	175 A2 / 168 A8, 20 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestar 344	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted, Vulcanization errors	





Notes and features

- The Alliance Forestar 344 is a powerful forestry tyre for CTL machines.
- The steel-reinforced nylon casing, the special rubber compound, as well as the reinforced sidewalls, protect the tyre against punctures.
- The traction tread pattern with low-angled lugs provides excellent grip and good self-cleaning thanks to wide gaps between the lugs.
- Due to the close spacing of the lugs in the centre of the tread, the rolling resistance can be reduced on hard surfaces.
- Matching chains and ribbons are available on the market.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	72200451
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	209,40
Recommended rim size	24.00
Maximum air pressure [bar].	5,00
Section width (mm)	710
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	620
Rolling circumference [mm].	4016
Tread depth (mm)	50,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A2	6900	10		5,00	
168 A8	5600	40		5,00	