

TYRES

Product group	Tyres	
Item number	72200458	
Valid tyre size	710 / 45 - 26.5	
LI / SI / PR	180 A2 / 173 A8, 24 PR	
TL/TT	тт	
Brand	Nokian	
Tread pattern	Forest King F2	
type of damage	Dismounted	





Notes and features

- Robust and stable in challenging conditions in forests.
- Balanced shape and extremely high operational stability.
- Upright, rigid, hard-wearing sidewalls and robust tread.
- Effective puncture protection through steel inserts in the tread.



Technical Informations

Item number	72200458
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	180 A2 / 173 A8, 24 PR
TL/TT	тт
Brand	Nokian
Tread pattern	Forest King F2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	235,13
Recommended rim size	24.00
Maximum air pressure [bar].	6,00
Section width (mm)	710
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	621
Rolling circumference [mm].	4084
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 A2	8000	10		6,00	
173 A8	6500	40		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.