

TYRES

Product group	Tyres	
Item number	72200471	
Valid tyre size	12.4 - 16	
LI / SI / PR	121 A8, 10 PR	
TL/TT	тт	
Brand	Alliance	
Tread pattern	316	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted,Runout	



Notes and features

- Tyre for soil-friendly use.
- Strong nylon construction.

 Use in fruit cultivation, lawn care, also suitable for light construction site vehicles.



Technical Informations

Item number	72200471
Valid tyre size	12.4 - 16
LI / SI / PR	121 A8, 10 PR
TL/TT	тт
Brand	Alliance
Tread pattern	316
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	31,94
Recommended rim size	11
Permitted rim size	10
Maximum air pressure [bar].	3,50
Section width (mm)	315
Outer diameter of tyre [mm].	931
Stat. radius (SLR) [mm]	429
Rolling circumference [mm].	2783
Tread depth (mm)	16,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 A8	1450	40		3,50	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.