

#### **TYRES**

Product group	Tyres
Item number	72200475
Valid tyre size	520 / 85 R 42
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Sonderpostenkategorie	Damaged
type of damage	Hole in the flank



#### Mitas

### Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.



## **Technical Informations**

Item number	72200475
Valid tyre size	520 / 85 R 42
Alternative size 1	20.8R42
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	203,20
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	537
Outer diameter of tyre [mm].	1966
Stat. radius (SLR) [mm]	896
Rolling circumference [mm].	5878
Tread depth (mm)	54,0
Number of lugs	22x2
Lug width (mm)	52
E-Ready	No

# **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		2,40	
162 B	4750	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.