

WHEELS

Product group	Wheels
Item number	72300093
Valid wheel size	600 / 50 - 22.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	20.00 x 22.5
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-50
Load capacity complete wheel [kg]	5150
Speed complete wheel [km/h]	40
Sonderpostenkategorie	Second hand goods
type of damage	Runout



Technical Informations

LI / SI / PR	153 A8 / 165 A8, 16 PR
Load capacity 1 [kg]	3650
Speed 1 [km/h].	40
Load capacity 2 [kg]	5150
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	162,68
Section width (mm)	600
Stat. radius (SLR) [mm]	510
Rolling circumference [mm].	3470

Tread depth (mm)	40,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	250
E-Ready	No
Load capacity of rim 1 [kg]	7070
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5310
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,60
Type of drive	Towed axle
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve

Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade