

TYRES

Product group	Tyres
Item number	72300099
Valid tyre size	540 / 65 R 28
LI / SI / PR	160 A8 / 155 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
Sonderpostenkategorie	Disassembled
type of damage	Irregular run



Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

Technical Informations

Item number	72300099
Valid tyre size	540 / 65 R 28
LI / SI / PR	160 A8 / 155 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	131,94
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	3,20
Section width (mm)	550
Outer diameter of tyre [mm].	1412
Stat. radius (SLR) [mm]	649
Rolling circumference [mm].	4266
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	328.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		3,20	
155 D	3875	65		3,20	