

## WHEELS

Product group	Wheels
Item number	72300133
Valid wheel size	15.0 / 55 - 17
Brand	BKT
Tread pattern	AW 705
Valid rim size	13.00 x 17
Rim connection	8/221/275
Bolt hole design	A3
Load capacity complete wheel [kg]	2575
Speed complete wheel [km/h]	40
Sonderpostenkategorie	Second hand goods
type of damage	Runout
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

LI / SI / PR	141 A8, 14 PR
Load capacity 1 [kg]	2575
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	55,97
Section width (mm)	381
Stat. radius (SLR) [mm]	391
Speed Radius Index (SRI)	410
Rolling circumference [mm].	2575

Tread depth (mm)	12,0
E-Ready	No
Load capacity of rim 1 [kg]	3400
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0

---

Valve angle [°]
-----------------

gerade
--------

---