

TYRES

Product group	Tyres
Item number	72300156
Valid tyre size	18.4 - 28
LI / SI / PR	157 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459
Sonderpostenkategorie	DOT
type of damage	DOT



Notes and features

- The strong nylon carcass & the special rubber compound make the tyre particularly resistant to breaks, punctures & similar damage.
- Extra wide and overlapping lugs in the center of the tread.
- Ideal for industrial use such as on backhoe loaders.

Technical Informations

Item number	72300156
Valid tyre size	18.4 - 28
LI / SI / PR	157 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	107,25
Recommended rim size	DW16L
Permitted rim size	DW15L
Maximum air pressure [bar].	2,50
Section width (mm)	472
Outer diameter of tyre [mm].	1475
Stat. radius (SLR) [mm]	664
Rolling circumference [mm].	4495
Tread depth (mm)	30,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		2,50	