

TYRES

Product group	Tyres
Item number	72300237
Valid tyre size	12.5 - 20
LI / SI / PR	132 G, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	317
Sonderpostenkategorie	Disassambled
type of damage	Dismounted,Runout





Notes and features

- Bias multi-purpose tyre for the most varied fields of application on a wide range of machines.
- Traction tread pattern for good traction and self-cleaning, even in difficult operation and weather conditions.
- Centrally-located tread bars for good vehicle handling on roads
- Approved up to 90 km/h (G Speed Index).
- For longer, free-rolling use, mounting against the rolling direction is recommended.



Technical Informations

Item number	72300237
Valid tyre size	12.5 - 20
LI / SI / PR	132 G, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	317
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	45,45
Recommended rim size	11
Maximum air pressure [bar].	3,50
Section width (mm)	325
Outer diameter of tyre [mm].	1040
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3090
Tread depth (mm)	24,3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 G	2000	90		3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.