

TYRES

Product group	Tyres	
Item number	72300259	
Valid tyre size	710 / 70 R 38	
LI / SI / PR	166 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Agrimax RT 765M	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted,Irregular run	



Notes and features

- The BKT Agrimax RT 765M is a 70 series radial tyre for tillage, field and transport use, grape harvesting and other applications.
- Its large contact area provides very good traction with low soil compaction.
- The tyre is characterised by very good self-cleaning properties.



Technical Informations

Item number	72300259
Valid tyre size	710 / 70 R 38
LI / SI / PR	166 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765M
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	230,23
Recommended rim size	DW23B
Maximum air pressure [bar].	1,60
Section width (mm)	716
Outer diameter of tyre [mm].	1959
Stat. radius (SLR) [mm]	859
Rolling circumference [mm].	5751
Tread depth (mm)	59,0
Number of lugs	20x2
Lug width (mm)	47
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.