

TYRES

Product group	Tyres
Item number	72300274
Valid tyre size	23.5 R 25
LI / SI / PR	195 A2 / 185 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41



Notes and features

- The improved tread design provides maximum traction.
- All steel carcass with reinforced steel belt ply provides excellent stability and puncture resistance.
- The special tread compound (C.R. = Cut Resistance) offers best cut resistance in combination with excellent mileage and wear properties.
- Especially suitable for use on wheel loaders and dumpers.
- Important: Mounting only permitted on multi-part rim.

Technical Informations

Item number	72300274
Valid tyre size	23.5 R 25
LI / SI / PR	195 A2 / 185 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41
TRA Code	E4/L4
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	382,05
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	5,00
Section width (mm)	615
Outer diameter of tyre [mm].	1611
Stat. radius (SLR) [mm]	725
Rolling circumference [mm].	4790
Tread depth (mm)	53,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
195 A2	12150	10	Loader dozer	5,00	
185 B	9250	50	Transport	5,00	