

WHEELS

Product group	Wheels
Item number	72300276
Valid wheel size	700 / 50 - 26.5
Brand	BKT
Tread pattern	Flotation 648
Valid rim size	AG 24.00 x 26.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	6700
Speed complete wheel [km/h]	40
type of damage	Runout



Technical Informations

Assembly Item no. Tyres	• 15712855
LI / SI / PR	162 A8 / 174 A8, 16 PR
Load capacity 1 [kg]	4750
Speed 1 [km/h].	40
Load capacity 2 [kg]	6700
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	232,35

ECE regulation number	ECE 106
Section width (mm)	700
Stat. radius (SLR) [mm]	581
Speed Radius Index (SRI)	575
Rolling circumference [mm].	4017
Tread depth (mm)	26,0
E-Ready	No
Assembly Item no. Rim	• 32012903
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade