

TYRES

Product group	Tyres
Item number	72300284
Valid tyre size	20.5 R 25
LI / SI / PR	177 B / 193 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 22
Sonderpostenkategorie	Disassembled
type of damage	Dismounted



Notes and features

- The BKT Earthmax SR 22 is an EM radial tyre for wheel loaders in winter use on snowy and icy surfaces
- The all-steel construction provides particular durability
- The block pattern with its large contact area provides good traction and stability

Technical Informations

Item number	72300284
Valid tyre size	20.5 R 25
LI / SI / PR	177 B / 193 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 22
TRA Code	E2/L2
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	232,45
Recommended rim size	17.00/2.0
Maximum air pressure [bar].	6,50
Section width (mm)	525
Outer diameter of tyre [mm].	1490
Stat. radius (SLR) [mm]	640
Rolling circumference [mm].	4315
Tread depth (mm)	32,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 B	7300	50	Transport	5,25	
193 A2	11500	10	Loader dozer	6,50	