

## TYRES

Product group	Tyres
Item number	72300299
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 L, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 08
Sonderpostenkategorie	Damaged
type of damage	Cut in the flank



**WINDPOWER**  
Get Your Job Done

## Notes and features

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

## Technical Informations

Item number	72300299
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 L, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 08
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	48,60
Recommended rim size	7.50
Permitted rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	252
Outer diameter of tyre [mm].	1022
Stat. radius (SLR) [mm]	478
Rolling circumference [mm].	3117
Tread depth (mm)	15,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 L	2800	120	Single	9,00	
142 L	2650	120	Twin	9,00	