

TYRES

Product group	Tyres
Item number	72300305
Valid tyre size	IF 600 / 70 R 30
LI / SI / PR	165 D / 162 E
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Sirio
Sonderpostenkategorie	Disassembled
type of damage	Dismounted,Irregular run



Notes and features

- New radial tyre for powerful tractors over 250 hp. Thanks to Speed Index E, this tyre allows high load capacities at speeds up to 70 km/h.
- The constant and uniform contact area reduces rolling resistance and fuel consumption
- Excellent ride comfort due to flexible sidewalls
- The special casing design with 6 polyester belts provides superb stability on the road and in the field
- A new sidewall compound and improved bead result in perfect heat dissipation

Technical Informations

Item number	72300305
Valid tyre size	IF 600 / 70 R 30
LI / SI / PR	165 D / 162 E
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Sirio
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	196,54
Recommended rim size	DW21B
Permitted rim size	DW20B
Maximum air pressure [bar].	2,40
Section width (mm)	603
Outer diameter of tyre [mm].	1602
Stat. radius (SLR) [mm]	713
Rolling circumference [mm].	4759
Tread depth (mm)	58,0
Number of lugs	20x2
Lug width (mm)	43
Tyre capacity 75% [ltr.]	456.08
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		2,40	
162 E	4750	70		2,40	