## Bohnenkamp Moving Professionals

#### **TYRES**

Product group	Tyres	
Item number	72300310	
Valid tyre size	VF 270 / 95 R 38	
LI / SI / PR	141 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 363 +	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted,Cut in the flank	





#### Notes and features

- The Alliance 363+ is a VF row crop tyre for heavy, self-. propelled field sprayers and tractors.
- It offers up to 40% higher load capacity at the same • inflation pressure or the same load capacity at up to 40% reduced inflation pressure compared with a standard tyre.
- The directional tread pattern design, divided in separate . blocks, enables good grip on soft surfaces.
- The increased number of lugs and block distribution on • the tread pattern ensure good ride comfort and low rolling resistance on roads.
- Its large contact area provides high traction, reduced fuel • consumption and low soil compaction.
- The steel belted casing enables uniform ground pressure . distribution and protection against damages, thus ensuring a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

	70000010
Item number	72300310
Valid tyre size	VF 270 / 95 R 38
LI / SI / PR	141 D
TL/TT	ть
Brand	Alliance
Tread pattern	Agriflex 363 +
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	73,70
Recommended rim size	W9
Permitted rim size	W10
Maximum air pressure [bar].	2,40
Section width (mm)	278
Outer diameter of tyre [mm].	1476
Stat. radius (SLR) [mm]	681
Rolling circumference [mm].	4432
Tread depth (mm)	35,0
Number of lugs	32x2
Tyre capacity 75% [ltr.]	139.5
Guarantee period	10 years
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 D	2575	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.