Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	72300321	
Valid tyre size	480 / 70 R 30	
LI / SI / PR	150 A8 / 144 E	
TL/TT	TL	
Brand	Alliance	
Tread pattern	370	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted,Runout	





Notes and features

- Agricultural wide-base tyre of the 70 series for tractors in • the low-performance range up to large tractors with over 200 hp.
- All-round tyre for use on farmland and grassland.
- Offers higher load capacities with the same inflation . pressure in comparison to 85 standard tyres.
- R-1W drive tread pattern with higher tread depth for • improved traction and high mileage.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	72300321
Valid tyre size	480 / 70 R 30
Alternative size 1	19.5LR30
LI / SI / PR	150 A8 / 144 E
TL/TT	TL
Brand	Alliance
Tread pattern	370
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	112,14
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	2,40
Section width (mm)	479
Outer diameter of tyre [mm].	1474
Stat. radius (SLR) [mm]	674
Rolling circumference [mm].	4491
Tread depth (mm)	46,0
Number of lugs	17x2
Lug width (mm)	37
Tyre capacity 75% [ltr.]	292.5
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		2,40	
144 E	2800	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.