

TYRES

Product group	Tyres
Item number	72300324
Valid tyre size	480 / 80 R 46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Sonderpostenkategorie	Damaged
type of damage	Stud damage



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	72300324
Valid tyre size	480 / 80 R 46
Alternative size 1	18.4R46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	188,66
Recommended rim size	DW16A
Permitted rim size	W16A, DD16, W16L, DD16L, DW16L
Maximum air pressure [bar].	2,40
Section width (mm)	479
Outer diameter of tyre [mm].	1936
Stat. radius (SLR) [mm]	895
Rolling circumference [mm].	5871
Tread depth (mm)	54,0
Number of lugs	24x2
Lug width (mm)	41
Tyre capacity 75% [litr.]	451.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		2,40	
158 B	4250	50		2,40	