

TYRES

Product group	Tyres
Item number	72300370
Valid tyre size	28 L - 26
LI / SI / PR	165 A6, 20 PR
TL/TT	TL
Brand	Nokian
Tread pattern	Logger King LS-2
Sonderpostenkategorie	Disassembled
type of damage	Dismounted



Notes and features

- The Nokian Logger King LS-2 was specially developed for skidders working in the toughest conditions.
- Due to its strong, high-strength and steel-reinforced casing in the tread and shoulder area, the tyre is particularly resistant to damages.
- The particularly hard-wearing rubber compound is ideal for demanding forestry use.
- The structure of the tyre bead with a seamless circumferential steel core enables easier mounting and even pressure distribution on the rim flange.
- The rubber compound in the bead area reduces the possibility of tyre slip to a minimum.

Technical Informations

Item number	72300370
Valid tyre size	28 L - 26
LI / SI / PR	165 A6, 20 PR
TL/TT	TL
Brand	Nokian
Tread pattern	Logger King LS-2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	296,93
Recommended rim size	25
Maximum air pressure [bar].	2,80
Section width (mm)	714
Outer diameter of tyre [mm].	1644
Stat. radius (SLR) [mm]	733
Rolling circumference [mm].	4932
Tread depth (mm)	58,0
Number of lugs	15x2
Tyre capacity 75% [ltr.]	585
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 A6	5150	30		2,40	
	7250	10		2,80	