

TYRES

Product group	Tyres
Item number	72300383
Valid tyre size	VF 480 / 80 R 50
LI/SI/PR	179 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Spargo
Sonderpostenkategorie	Damaged
type of damage	Stud damage





Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.



Technical Informations

Item number	72300383
Valid tyre size	VF 480 / 80 R 50
LI / SI / PR	179 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	236,80
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	3,60
Section width (mm)	479
Outer diameter of tyre [mm].	2038
Stat. radius (SLR) [mm]	947
Rolling circumference [mm].	6224
Tread depth (mm)	43,5
Number of lugs	32x2
Tyre capacity 75% [ltr.]	466.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.