

TYRES

Product group	Tyres	
Item number	72400002	
Valid tyre size	710 / 75 R 34	
LI / SI / PR	178 A8 / 178 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agristar 375	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted, Vulcanization errors	





Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.



Technical Informations

Item number	72400002
Valid tyre size	710 / 75 R 34
LI / SI / PR	178 A8 / 178 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	319,32
Recommended rim size	23
Permitted rim size	21
Maximum air pressure [bar].	3,20
Section width (mm)	720
Outer diameter of tyre [mm].	1945
Stat. radius (SLR) [mm]	880
Rolling circumference [mm].	5789
Tread depth (mm)	58,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	832.5
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40		3,20	
178 B	7500	50		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.