Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres | | |
|-----------------------|-----------------------------------|--|--|
| Item number | 72400011 | | |
| Valid tyre size | 600 / 50 R 22.5 | | |
| LI / SI / PR | 166 F | | |
| TL/TT | TL | | |
| Brand | Alliance | | |
| Tread pattern | 390 | | |
| Sonderpostenkategorie | Disassambled | | |
| type of damage | Dismounted,Scratcher in the flank | | |





Notes and features

- Ideal for longer transport and grassland use.
- Block tread pattern for smooth handling on long road journeys and soil protection when driving on grassland.
- Low rolling resistance for minimum fuel consumption.
- High tread depth for a long service life.
- Steel belt reinforcement for high load capacities and improved stability.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 72400011 |
|------------------------------|-----------------|
| Valid tyre size | 600 / 50 R 22.5 |
| LI / SI / PR | 166 F |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 390 |
| Carcass properties | All-Steel |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 138,16 |
| Recommended rim size | 20.00 |
| Maximum air pressure [bar]. | 6,00 |
| Section width (mm) | 585 |
| Outer diameter of tyre [mm]. | 1180 |
| Stat. radius (SLR) [mm] | 539 |
| Rolling circumference [mm]. | 3510 |
| Tread depth (mm) | 25,0 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 166 F | 5300 | 80 | | 6,00 | |