

TYRES

Product group	Tyres
Item number	72400017
Valid tyre size	900 / 60 R 32 CHO
LI / SI / PR	185 A8 / 182 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Sonderpostenkategorie	Damaged
type of damage	Cut in the flank



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

Technical Informations

Item number	72400017
Valid tyre size	900 / 60 R 32 CHO
LI / SI / PR	185 A8 / 182 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	406,00
Recommended rim size	DW27B
Permitted rim size	DW28B, DW30B
Maximum air pressure [bar].	4,00
Section width (mm)	886
Outer diameter of tyre [mm].	1910
Stat. radius (SLR) [mm]	875
Rolling circumference [mm].	5775
Tread depth (mm)	58,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 A8	9250	40		4,00	
182 B	8500	50		4,00	