

TYRES

Product group	Tyres
Item number	72400024
Valid tyre size	VF 800 / 60 R 32
LI / SI / PR	188 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 389 +
Sonderpostenkategorie	Disassambled
type of damage	Dismounted,Flap damage





Notes and features

- The Alliance Agriflex 389 + is a VF tyre for agricultural trailers and trucks converted for agricultural use.
- The tyre enables very high loading capacities at extremely low inflation pressures.
- Its contact area, which is 25% larger compared to a standard tyre, provides excellent traction and reduced fuel consumption.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- Its special tread pattern provides good grip and outstanding self-cleaning properties.
- Its casing, reinforced by 3 steel belts is characterised by durability and resistance to damage.



Technical Informations

Item number	72400024
Valid tyre size	VF 800 / 60 R 32
LI / SI / PR	188 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 389 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	278,70
Recommended rim size	DW27B
Permitted rim size	TW27B
Maximum air pressure [bar].	2,80
Section width (mm)	800
Outer diameter of tyre [mm].	1800
Stat. radius (SLR) [mm]	778
Rolling circumference [mm].	5465
Tread depth (mm)	26,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	877.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
188 D	10000	65		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.