

TYRES

Product group	Tyres	
Item number	72400036	
Valid tyre size	480 / 70 R 38	
LI / SI / PR	145 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Agrimax RT 765	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted,Runout	



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.



Technical Informations

Item number	72400036
Valid tyre size	480 / 70 R 38
LI / SI / PR	145 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	138,08
Recommended rim size	W15L
Permitted rim size	W14L, W16L
Maximum air pressure [bar].	1,60
Section width (mm)	479
Outer diameter of tyre [mm].	1681
Stat. radius (SLR) [mm]	764
Rolling circumference [mm].	5055
Tread depth (mm)	50,0
Number of lugs	22x2
Lug width (mm)	40
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 D	2900	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.