

## WHEELS

Product group	Wheels
Item number	72400047
Valid wheel size	500 / 50 R 17
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	16.00 x 17
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	3250
Speed complete wheel [km/h]	65
Sonderpostenkategorie	Damaged
type of damage	Crack in the flank
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

LI / SI / PR	149 D / 146 E
Load capacity 1 [kg]	3250
Speed 1 [km/h].	65
Load capacity 2 [kg]	3000
Speed 2 [km/h].	70
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	0,00

ECE regulation number	ECE 106
Section width (mm)	503
Stat. radius (SLR) [mm]	424
Rolling circumference [mm].	2913
Tread depth (mm)	15,0
E-Ready	No
Load capacity of rim 1 [kg]	3750
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	70
Maximum air pressure [bar].	5,00
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

---

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade