

## **TYRES**

Product group	Tyres
Item number	72400073
Valid tyre size	445 / 70 R 24
LI / SI / PR	151 G
TL/TT	TL
Brand	Alliance
Tread pattern	570
Sonderpostenkategorie	Damaged
type of damage	Flap damage





## Notes and features

- Radial multipurpose tyre for a wide variety of applications.
- Specially suited for use on harvesters.
- Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
- Radial textile casing with steel belt reinforcement.



## **Technical Informations**

Item number	72400073
Valid tyre size	445 / 70 R 24
LI / SI / PR	151 G
TL/TT	TL
Brand	Alliance
Tread pattern	570
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	92,05
Recommended rim size	15
Permitted rim size	14,13
Maximum air pressure [bar].	4,00
Section width (mm)	445
Outer diameter of tyre [mm].	1234
Stat. radius (SLR) [mm]	564
Rolling circumference [mm].	3670
Tread depth (mm)	32,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 G	3450	90		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.