Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres
Item number	72400075
Valid tyre size	620 / 70 R 42
LI / SI / PR	173 A8 / 170 B
TL/TT	TL
Brand	Alliance
Tread pattern	360
Sonderpostenkategorie	Damaged
type of damage	Cut in the flank





Notes and features

- Universal agricultural wide-base tyre for tractors, harvesters and other farm machinery.
- High air volume for increased load capacity and low ground pressure.
- Adapted lugs for massive traction and very good ride comfort at the same time.
- Strong radial casing with reinforced bead and sidewall for a long service life.

Bohnenkamp Moving Professionals

Technical Informations

Item number	72400075
Valid tyre size	620 / 70 R 42
LI / SI / PR	173 A8 / 170 B
TL/TT	TL
Brand	Alliance
Tread pattern	360
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	260,50
Recommended rim size	DW20
Permitted rim size	DW20B
Maximum air pressure [bar].	2,70
Section width (mm)	650
Outer diameter of tyre [mm].	1940
Stat. radius (SLR) [mm]	887
Rolling circumference [mm].	5795
Tread depth (mm)	52,0
Number of lugs	24x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		2,70	
170 B	6000	50		2,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.