

RIMS

| | |
|-----------------------|---------------------|
| Product group | Rims |
| Item number | 72400090 |
| Valid rim size | AG 24.00 x 26.5 TH2 |
| Rim connection | 8/221/275 |
| Bolt hole design | A2 |
| Rim colour | Silver |
| Brand | GKN |
| Rim series | Profiline |
| Sonderpostenkategorie | Disassembled |
| type of damage | Dismounted |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 8570 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 6300 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 65 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 85,00 |
| Hump | TH2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |

| | |
|--------------------------------|----------------|
| Cavity Sealed | No |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 8 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 221 |
| Bolt hole circle diameter [mm] | 275 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |