

TYRES

Product group	Tyres
Item number	72400095
Valid tyre size	VF 480 / 80 R 50
LI / SI / PR	179 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Sonderpostenkategorie	Damaged
type of damage	Flap damage



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

Item number	72400095
Valid tyre size	VF 480 / 80 R 50
LI / SI / PR	179 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	236,80
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	3,60
Section width (mm)	479
Outer diameter of tyre [mm].	2038
Stat. radius (SLR) [mm]	947
Rolling circumference [mm].	6224
Tread depth (mm)	43,5
Number of lugs	32x2
Tyre capacity 75% [ltr.]	466.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		3,60	