

## **TYRES**

Product group	Tyres
Item number	72400101
Valid tyre size	540 / 65 - 38
LI / SI / PR	160 A2 / 153 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360
Sonderpostenkategorie	Disassambled
type of damage	Dismounted





## Notes and features

- The Alliance Forestry 360 is a forestry tyre for light forestry applications.
- Its low lug angles provide excellent traction.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls and tread pattern, the tyre is particularly robust.
- The tyre can also be used for agro-industrial applications.



## **Technical Informations**

Item number	72400101
Valid tyre size	540 / 65 - 38
LI / SI / PR	160 A2 / 153 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	202,00
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	518
Outer diameter of tyre [mm].	1699
Stat. radius (SLR) [mm]	793
Rolling circumference [mm].	5125
Tread depth (mm)	50,0
Number of lugs	23x2
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A2	4500	10		2,40	
153 A8	3650	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.