

TYRES

Product group	Tyres	
Item number	72400102	
Valid tyre size	600 / 65 R 38	
LI / SI / PR	162 A8 / 159 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agristar 365	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted,Runout	





Notes and features

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.



Technical Informations

Item number	72400102
Valid tyre size	600 / 65 R 38
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	181,16
Recommended rim size	DW20B
Permitted rim size	DW18
Maximum air pressure [bar].	2,40
Section width (mm)	594
Outer diameter of tyre [mm].	1745
Stat. radius (SLR) [mm]	782
Rolling circumference [mm].	5284
Tread depth (mm)	49,0
Lug width (mm)	46-49
Tyre capacity 75% [ltr.]	478
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		2,40	
159 D	4375	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.