

TYRES

Product group	Tyres
Item number	72400107
Valid tyre size	35 / 65 R 33
LI / SI / PR	229 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 315 CS
Sonderpostenkategorie	Damaged
type of damage	Cut in the tread



Notes and features

- The BKT Earthmax SR 315 CS was specially developed for loader use in mining.
- Due to its very good cut resistance, the tyre is extremely puncture-proof and durable.
- Thanks to the L3S tread pattern, the tyre is also protected from overheating, even over longer distances.
- The high lateral stability provides high ride comfort.
- The smooth tread with the chamfered shoulder (CS = Chamfered Shoulder) enables ideal adaptation for tyre chains.
- The tyre is ideal for use in combination with the Earthmax SR 55.
- Reason: the diameters of the tyres: Earthmax SR 315 CS with chain and Earthmax SR 55 without chain are the same.

Technical Informations

Item number	72400107
Valid tyre size	35 / 65 R 33
LI / SI / PR	229 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 315 CS
TRA Code	L3S
Star Rating	***
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	975,00
Recommended rim size	28.00/3.5
Maximum air pressure [bar].	8,00
Section width (mm)	880
Outer diameter of tyre [mm].	1948
Stat. radius (SLR) [mm]	867
Rolling circumference [mm].	5886
Tread depth (mm)	42,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
229 A2	32500	10	Loader dozer	8,00	