

TYRES

Product group	Tyres
Item number	72400117
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Sonderpostenkategorie	Damaged
type of damage	Cut in the tread



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	72400117
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	30,67
Recommended rim size	9.0
Permitted rim size	11
Maximum air pressure [bar].	3,70
Section width (mm)	308
Outer diameter of tyre [mm].	965
Stat. radius (SLR) [mm]	432
Rolling circumference [mm].	2827
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		5,00	