

TYRES

Product group	Tyres
Item number	72400143
Valid tyre size	525 / 65 R 20.5
LI / SI / PR	173 F, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 699
Sonderpostenkategorie	Disassembled
type of damage	Dismounted,Runout



Notes and features

- The BKT Ridemax FL 699 is a radial tyre for agricultural trailers and tankers used mainly for road transport.
- The tyre enables high loading capacities, good driving control and ride comfort.
- The all-steel casing and reinforced bead provide excellent stability and a long service life.
- The tyre also performs superbly in field applications.

Technical Informations

Item number	72400143
Valid tyre size	525 / 65 R 20.5
LI / SI / PR	173 F, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 699
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	140,00
Recommended rim size	16.00
Permitted rim size	18.00
Maximum air pressure [bar].	8,00
Section width (mm)	518
Outer diameter of tyre [mm].	1200
Stat. radius (SLR) [mm]	544
Rolling circumference [mm].	3678
Tread depth (mm)	18,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 F	6500	80		8,00	