# Bohnenkamp Moving Professionals

### **TYRES**

| Product group         | Tyres                     |  |
|-----------------------|---------------------------|--|
| Item number           | 72400164                  |  |
| Valid tyre size       | 650 / 75 R 38             |  |
| LI / SI / PR          | 169 D                     |  |
| TL/TT                 | TL                        |  |
| Brand                 | Alliance                  |  |
| Tread pattern         | Agristar 378 XL           |  |
| Sonderpostenkategorie | Damaged                   |  |
| type of damage        | Puncture at tyre shoulder |  |





#### Notes and features

- Super volume tyre for high-performance tractors from • approx. 200 hp and harvesters.
- Designed for versatile applications. •
- Comfortable on-road handling and high traction combined with very good self-cleaning properties in field operations.
- Built-in steel belts for extra stability, protection against . punctures and large contact area.
- Innovative rubber compound for a longer service life and • flexible sidewalls (for air pressure adjustment).

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

| Item number                  | 72400164        |
|------------------------------|-----------------|
| Valid tyre size              | 650 / 75 R 38   |
| LI / SI / PR                 | 169 D           |
| TL/TT                        | TL              |
| Brand                        | Alliance        |
| Tread pattern                | Agristar 378 XL |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| Nettogewicht [kg] (gültig)   | 247,62          |
| Recommended rim size         | 23              |
| Maximum air pressure [bar].  | 2,40            |
| Section width (mm)           | 671             |
| Outer diameter of tyre [mm]. | 1930            |
| Stat. radius (SLR) [mm]      | 871             |
| Rolling circumference [mm].  | 5730            |
| Tread depth (mm)             | 62,0            |
| Number of lugs               | 19x2            |
| Tyre capacity 75% [ltr.]     | 713             |
| Guarantee period             | 7 years         |
| E-Ready                      | No              |

#### Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 169 D | 5800               | 65           |               | 2,40                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.