

TYRES

Product group	Tyres
Item number	72400169
Valid tyre size	12.5 - 18
LI / SI / PR	128 G, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 567
Sonderpostenkategorie	Damaged
type of damage	Puncture at tyre shoulder



GROWING TOGETHER

Notes and features

- The BKT MP 567 is a multi purpose tyre offering maximum flexibility.
- The tyre features good traction in all weathers.
- Suitable for on- and off-road use.

- The open tread pattern allows for efficient self-cleaning.
- Suitable for use on vehicles such as Unimogs, backhoe loaders, dumpers, etc.



Technical Informations

Item number	72400169
Valid tyre size	12.5 - 18
LI / SI / PR	128 G, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 567
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	0,00
Recommended rim size	11
Permitted rim size	12SDC
Maximum air pressure [bar].	3,00
Section width (mm)	325
Outer diameter of tyre [mm].	990
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	2940
Tread depth (mm)	22,0
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 G	1800	90		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.