

## **TYRES**

Product group	Tyres
Item number	72400177
Valid tyre size	395 / 85 R 20
LI / SI / PR	168 J
TL/TT	TL
Brand	ВКТ
Tread pattern	Earthmax SR 33
Sonderpostenkategorie	Disassambled
type of damage	Dismounted,Runout



## Notes and features

- The BKT Earthmax SR 33 is a radial MPT tyre
- The block pattern provides very good traction on soft, sandy or muddy ground
- The wide spaces between the tread pattern blocks enable very good self-cleaning
- The strong, all-steel casing ensures excellent cut resistance and a long service life



## **Technical Informations**

Item number	72400177
Valid tyre size	395 / 85 R 20
LI / SI / PR	168 J
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	108,10
Recommended rim size	10.00W
Permitted rim size	10.00HF
Maximum air pressure [bar].	8,50
Section width (mm)	394
Outer diameter of tyre [mm].	1184
Stat. radius (SLR) [mm]	538
Rolling circumference [mm].	3589
Tread depth (mm)	25,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 J	5600	100		8,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.