

TYRES

Product group	Tyres
Item number	72400180
Valid tyre size	205 / 70 R 15 C
LI / SI / PR	106 / 104 R, 8 PR
TL/TT	TL
Brand	GT Radial
Tread pattern	Maxmiler Pro
Sonderpostenkategorie	DOT
type of damage	DOT



Bohnenkamp
Moving Professionals

GT RADIAL

Notes and features

- The Maxmiler Pro is a trailer tyre
- The flat tyre contour provides a long service life of the tyre
- Its tread pattern with larger shoulder blocks with integrated sipes and the circumferential groove with sipes guarantee driving stability on dry and wet roads

Technical Informations

Item number	72400180
Valid tyre size	205 / 70 R 15 C
LI / SI / PR	106 / 104 R, 8 PR
TL/TT	TL
Brand	GT Radial
Tread pattern	Maxmiler Pro
Rolling resistance	C
Wet grip	C
Rolling noise [db].	71
Rolling noise level	B
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	12,80
Recommended rim size	6.00J
Permitted rim size	5.50J, 6.50J
Maximum air pressure [bar].	4,50
Section width (mm)	209
Outer diameter of tyre [mm].	669
Stat. radius (SLR) [mm]	303
Rolling circumference [mm].	2040
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 R	950	170	Single	4,50	
104 R	900	170	Twin	4,50	