Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	72400195
Valid tyre size	VF 750 / 60 R 30.5
LI / SI / PR	183 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 389 +
Sonderpostenkategorie	Damaged
type of damage	Stud damage





Notes and features

- The Alliance Agriflex 389 + is a VF tyre for agricultural • trailers and trucks converted for agricultural use.
- The tyre enables very high loading capacities at extremely • low inflation pressures.
- Its contact area, which is 25% larger compared to a standard tyre, provides excellent traction and reduced fuel consumption.
- At the same time, soil compaction is reduced and the soil • is optimally protected.
- Its special tread pattern provides good grip and • outstanding self-cleaning properties.
- Its casing, reinforced by 3 steel belts is characterised by • durability and resistance to damage.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number 7	
	72400195
Valid tyre size	/F 750 / 60 R 30.5
LI / SI / PR 1	183 D
TL/TT T	rL
Brand A	Alliance
Tread pattern A	Agriflex 389 +
Carcass properties S	Steel Belted
Antistatic N	No
Tyre colour B	Black
Nettogewicht [kg] (gültig) 2	248,00
Recommended rim size A	AG24.00
Maximum air pressure [bar]. 2	2,80
Section width (mm) 7	780
Outer diameter of tyre [mm]. 1	1680
Stat. radius (SLR) [mm] 7	721
Rolling circumference [mm]. 5	5071
Tread depth (mm) 2	26,0
Number of lugs 2	26x2
Tyre capacity 75% [ltr.] 7	727.5
Guarantee period 1	LO years
E-Ready N	Νο

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
183 D	8750	65		2,80	
	11640	40			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.