

TYRES

Product group	Tyres
Item number	72400205
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	189 A2 / 182 A8, 24 PR
TL/TT	TT
Brand	Alliance
Tread pattern	Forestar 644 III
Sonderpostenkategorie	Damaged
type of damage	Stud damage



Notes and features

- The Alliance Forestar 644 III is a versatile forestry tyre for different applications.
- Its dual lug angles provide excellent grip and traction.
- Thanks to the improved steel belt casing and the special hexagonal bead technology, the tyre offers outstanding puncture resistance, stability, high loading capacities and low slip.
- The special shoulder design and curb-rib design of the sidewall provide stiffness and protection from side impacts.
- The large contact area ensures low soil compaction.
- The angled lugs form wide blocks in the centre of the tread to ensure stability and ride comfort.

Technical Informations

Item number	72400205
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	189 A2 / 182 A8, 24 PR
TL/TT	TT
Brand	Alliance
Tread pattern	Forestar 644 III
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	270,00
Recommended rim size	24.00
Maximum air pressure [bar].	6,00
Section width (mm)	750
Outer diameter of tyre [mm].	1490
Stat. radius (SLR) [mm]	683
Rolling circumference [mm].	4467
Tread depth (mm)	51,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	454.43
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
189 A2	10300	10		6,00	
182 A8	8500	40		6,00	