

TYRES

Product group	Tyres	
Item number	72400206	
Valid tyre size	580 / 70 R 42	
LI / SI / PR	158 D	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	ТМ700РТ	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted	





Notes and features

- The Trelleborg TM700 Progressive Traction is a new TM700 product line.
- Just like the TM700, it provides excellent self-cleaning properties, outstanding traction in the field and the best possible ride comfort on the road.
- Typical of the Progressive Traction are special double lugs that greatly increase traction when needed and should therefore increase the efficiency of the tyre.
- The tyre was developed specially for tractors in the performance range from 100 up to 240 hp.



Technical Informations

Item number	72400206
Valid tyre size	580 / 70 R 42
LI / SI / PR	158 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700PT
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	222,96
Recommended rim size	W18L
Permitted rim size	DW18L
Maximum air pressure [bar].	1,60
Section width (mm)	585
Outer diameter of tyre [mm].	1905
Stat. radius (SLR) [mm]	850
Rolling circumference [mm].	5695
Tread depth (mm)	60,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	519
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.