

## **TYRES**

| Product group         | Tyres          |  |
|-----------------------|----------------|--|
| Item number           | 72400214       |  |
| Valid tyre size       | 18.00 - 33     |  |
| LI / SI / PR          | 40 PR          |  |
| TL/TT                 | TL             |  |
| Brand                 | ВКТ            |  |
| Tread pattern         | Container King |  |
| Sonderpostenkategorie | Damaged        |  |
| type of damage        | Flap damage    |  |



## Notes and features

- The wide central rib creates a large contact surface and provides for outstanding stability when lifting heavy weights
- The strong casing and special hard-wearing running surface compound provide for excellent durability and a long service life
- Best suited for container handlers, such as reach stackers



## **Technical Informations**

| Item number                  | 72400214       |
|------------------------------|----------------|
| Valid tyre size              | 18.00 - 33     |
| LI / SI / PR                 | 40 PR          |
| TL/TT                        | TL             |
| Brand                        | BKT            |
| Tread pattern                | Container King |
| TRA Code                     | IND4           |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| Nettogewicht [kg] (gültig)   | 482,15         |
| Recommended rim size         | 13.00/2.5      |
| Maximum air pressure [bar].  | 10,00          |
| Section width (mm)           | 510            |
| Outer diameter of tyre [mm]. | 1895           |
| Stat. radius (SLR) [mm]      | 852            |
| Speed Radius Index (SRI)     | 550            |
| Rolling circumference [mm].  | 5820           |
| Tread depth (mm)             | 67,5           |
| Number of lugs               | 29x2           |
| E-Ready                      | No             |

## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
|       | 25000              | 25           |               | 10,00                       |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.