

TYRES

Product group	Tyres
Item number	72400245
Valid tyre size	750 / 65 R 26 CHO
LI / SI / PR	171 A8 / 171 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Sonderpostenkategorie	Damaged
type of damage	Flap damage



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

Technical Informations

Item number	72400245
Valid tyre size	750 / 65 R 26 CHO
Alternative size 1	28LR26
LI / SI / PR	171 A8 / 171 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	244,31
Recommended rim size	DW25B
Permitted rim size	DW23B
Maximum air pressure [bar].	3,20
Section width (mm)	764
Outer diameter of tyre [mm].	1636
Stat. radius (SLR) [mm]	713
Rolling circumference [mm].	4908
Tread depth (mm)	46,0
Number of lugs	18x2
Lug width (mm)	55
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
171 A8	6150	40		3,20	
171 B	6150	50		3,20	