# Bohnenkamp Moving Professionals

### **TYRES**

Product group	Tyres
Item number	72400258
Valid tyre size	440 / 65 R 24
LI / SI / PR	138 A8 / 135 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Sonderpostenkategorie	Disassambled
type of damage	Dismounted,Irregular run





#### Notes and features

- Agricultural radial wide tyre of the 65 series (70 series • with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large • contact area.
- Lug shape and arrangement allows optimum traction . power distribution.
- With 65 km/h approval, suitable for frequent road use. •

19.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	72400258
Valid tyre size	440 / 65 R 24
LI / SI / PR	138 A8 / 135 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	75,01
Recommended rim size	14
Permitted rim size	13
Maximum air pressure [bar].	2,40
Section width (mm)	446
Outer diameter of tyre [mm].	1187
Stat. radius (SLR) [mm]	547
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3526
Contact area [cm²]	1071
Tread depth (mm)	45,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	459.75
Guarantee period	7 years
E-Ready	No

19.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



#### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40		2,40	
135 D	2180	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.